

	-200 sion 1.0	griwecolor Stain primer Revision date 18-Oct-2024	Print date 18-Oct-202		
SE	CTION 1: Identificatior	of the substance/mixture and of the company/undertaking			
1.1	Product identifier				
	Trade name/designatior				
	FG0-200	griwecolor Stain primer colourless			
1.2	Polovant identified uses				
1.2	Relevant identified uses of the substance or mixture and uses advised against				
	Relevant identified uses				
	see as in techn. data she				
1.3	Details of the supplier o	t the safety data sheet			
	Supplier				
	griwecolor GmbH	T 10 7707 000 / 0			
	lm Wieselbrunnen 2 78199 Bräunlingen	Telephone: +49 7707 9904-0 E-mail: info@griwecolor.de			
	Germany				
	Department responsible	for information			
	E-mail (competent persor				
.4	Emergency telephone n				
	Emergency telephone nu				
	Only available during offic				
SE	CTION 2: Hazards ider				
2.1	Classification of the substance or mixture				
	Classification according	to Regulation (EC) No 1272/2008 [CLP]			
	The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].				
2.2	Label elements				
	Labelling according to Regulation (EC) No. 1272/2008 [CLP]				
	Hazard pictograms				
	not applicable				
	Signal word				
	not applicable				
	Hazard statements				
	not applicable	4-			
	Precautionary statemen	IS			
	not applicable	lehe Ware			
	Hazard components for	labelling			
	not applicable	•			
	Supplemental hazard in				
	EUH208	Contains 1,2-benzisothiazol-3(2H)-one, 2-methylisothiazol-3(2H)-one, react methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3- one (3:1). May pr			
	EUH210	Safety data sheet available on request.			
2.3	Other hazards				
	The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.				
SF	CTION 3. Composition	/information on ingredients.			
	•				
3.2	Mixtures				

J.Z WIXTURES

Description waterbased Dispersion

Hazardous ingredients

CAS No.	Substance name	
EC No.	REACH No.	weight-%



0-200 sion 1.0	griwecolor Stain primer Revision date 18-Oct-2024	Print date 18-Oct-2024
Index No.	Classification according to Regulation (EC) No 1272/2008 [CLP]	-
2634-33-5 220-120-9 613-088-00-6	1,2-benzisothiazol-3(2H)-one 01-2120761540-60 Acute Tox. 4 H302 / Skin Irrit. 2 H315 / Skin Sens. 1 H317 / Eye Dam. 1 H318 / Acute Tox. 2 H330 / Aquatic Acute 1 H400 / Aquatic Chronic 1 H410 Specific concentration limit (SCL) Skin Sens. 1 H317: >= 0,05 ATE (oral): = 532 mg/kg ATE (dermal): = 5,000 mg/kg	0,025 < 0,050
55965-84-9 - 613-167-00-5	reaction mass of 5-chloro-2- methyl-2H-isothiazol-3- one and 2-methyl-2H-isothiazol-3- one (3:1) Acute Tox. 3 H301 / Acute Tox. 2 H310 / Skin Corr. 1C H314 / Skin Sens. 1A H317 / Eye Dam. 1 H318 / Acute Tox. 2 H330 / Aquatic Acute 1 H400 (M = 100,00) / Aquatic Chronic 1 H410 (M = 100,00) / EUH071 Specific concentration limit (SCL) Eye Irrit. 2 H319: >= 0,06 / Skin Sens. 1A H317: >= 0,0015 / Eye Dam. 1 H318: >= 0,60 / Skin Irrit. 2 H315: >= 0,06 / Skin Corr. 1C H314: >= 0,60	
2682-20-4 220-239-6 613-326-00-9	2-methylisothiazol-3(2H)-one Acute Tox. 3 H301 / Acute Tox. 3 H311 / Skin Corr. 1B H314 / Skin Sens. 1A H317 / Eye Dam. 4 H318 / Acute Tox. 2 H330 / Aquatic Acute 1 H400 (M = 10,00) / Aquatic Chronic 1 H410 (M = 1,00) / EUH071 Specific concentration limit (SCL) Skin Sens. 1A H317: >= 0,0015 ATE (oral): 120 mg/kg ATE (dermal): 300 mg/kg ATE (inhalative): 0.134 mg/L (4 h)	< 0,025

Remark

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

Self-protection of the first aider

First aider: Pay attention to self-protection!

4.2 Most important symptoms and effects, both acute and delayed

Symptoms

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3 Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1 Extinguishing media

The product itself does not burn. **Suitable extinguishing media** alcohol resistant foam, Carbon dioxide (CO2), Powder, spray mist, (water) **Unsuitable extinguishing media** Strong water jet



FG0-200griwecolor Stain primerVersion 1.0Revision date 18-Oct-2024

5.2 Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage. Hazardous decomposition byproducts may form with exposure to high temperatures: Carbon dioxide (CO2), carbon monoxide, smoke, Nitrogen oxides (NOx).

5.3 Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Observe protective provisions (see section 7 and 8).

6.2 Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

For containment

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

For cleaning up

Clean using cleansing agents. Do not use solvents.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advices on safe handling

Avoid contact with skin, eyes and clothes. Avoid respiration of swarf. Personal protection equipment: see section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Advices on general occupational hygiene

When using do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

Storage class

LGK12 - non-combustible liquids that cannot be assigned to any of the above storage classes

Further information on storage conditions

Protect from heat and direct sunlight. Protect from frost. Take care of instructions on label.

7.3 Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No data available

Biological limit values

No data available

DNEL worker

CAS No.	Substance name	DNEL type	DNEL value
2634-33-5	1,2-benzisothiazol-3(2H)-one	DNEL long-term dermal (systemic)	0.966 mg/kg
2634-33-5	1,2-benzisothiazol-3(2H)-one	DNEL long-term inhalative (systemic)	6.81 mg/m ³
55965-84-9	reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3- one (3:1)	DNEL acute inhalative (local)	0.04 mg/m ³



-200 sion 1.0	griwecolor Stain primer Revision date 18-Oct-2024		Print date 18-Oct-202	
55965-84-9	reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3- one (3:1)	DNEL long-term inhalative (local)	0.02 mg/m ³	
DNEL Consume	Ľ	-		
CAS No.	Substance name	DNEL type	DNEL value	
2634-33-5	1,2-benzisothiazol-3(2H)-one	DNEL long-term inhalative (systemic)	1.2 mg/m ³	
2634-33-5	1,2-benzisothiazol-3(2H)-one	DNEL long-term dermal (systemic)	0.345 mg/kg	
55965-84-9	reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3- one (3:1)	DNEL acute inhalative (local)	0.04 mg/m ³	
55965-84-9	reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3- one (3:1)	DNEL long-term inhalative (local)	0.02 mg/m ³	
55965-84-9	reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3- one (3:1)	DNEL long-term oral (repeated)	0.09 mg/kg	
55965-84-9	reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3- one (3:1)	DNEL short-term oral (acute)	0.11 mg/kg	

PNEC

CAS No.	Substance name	PNEC type	PNEC Value
55965-84-9	reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3- one (3:1)	PNEC soil, freshwater	0.01 mg/kg
55965-84-9	reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3- one (3:1)	PNEC aquatic, freshwater	0.004 mg/L

8.2 Exposure controls

Provide good ventilation. This can be achieved with local or room suction.

Personal protection equipment

Respiratory protection

not applicable

Hand protection

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles: EN ISO 374

Skin protection

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Eye glasses with side protection: EN 166

Body protection

Wear suitable protective clothing.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

l	Physical state	Liquid
(Colour	refer to label
(Odour	characteristic
I	pH at 20 °C (100%)	7 - 8.8
I	Melting point/freezing point	not determined
l	Initial boiling point and boiling range	> 35 °C
I	Flash point	not applicable
t	flammability	not applicable
I	Lower explosion limit at 20°C	not determined
	Upper explosion limit at 20°C	not determined



FG0-200 Version 1.0	griwecolor Stain primer Revision date 18-Oct-2024	Print date 18-Oct-2024
Vapour pressure at 20°C	not determined	
Relative vapour density	not applicable	
Density at 20 °C	1.01 kg/l	
Water solubility at 20°C	completely miscible	
Partition coefficient: n-octano	l/water see section 12	
Ignition temperature in °C	not determined	
Decomposition temperature	not determined	
Kinematic viscosity at 20 °C:	20 mm²/s	
Dynamic viscosity:	20.12 mPas	
particle characteristics	not applicable	

9.2 Other information

not applicable

SECTION 10: Stability and reactivity

10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3 Possibility of hazardous reactions

Not applicable

10.4 Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5 Incompatible materials

No further relevant information available.

10.6 Hazardous decomposition products

Decomposition products in case of fire: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

1,2-benzisothiazol-3(2H)-one

LD50: oral (Rat): = 532 mg/kg

LD50: dermal (Rat): = 5,000 mg/kg

2-methylisothiazol-3(2H)-one

LD50: oral (Rat): 120 mg/kg

LD50: dermal (Rat): 300 mg/kg

LC50: inhalative (Rat): 0.134 mg/L (4 h)

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

Overall assessment on CMR properties

Based on available data, the classification criteria are not met.

STOT-single exposure



FG0-200	griwecolor Stain primer
Version 1.0	Revision date 18-Oct-2024

Print date 18-Oct-2024

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

11.2 Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 12: Ecological information

12.1 Toxicity

Based on available data, the classification criteria are not met.

Algae toxicity

1,2-benzisothiazol-3(2H)-one

ErC50: (Pseudokirchneriella subcapitata): = 0.11 mg/L

reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3- one (3:1) ErC50: (Pseudokirchneriella subcapitata): = 0.048 mg/L

Daphnia toxicity

1,2-benzisothiazol-3(2H)-one EC50 = 16.4 mg/L (48 h)

reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3- one (3:1)

EC50 = 0.1 mg/L (48 h)

Fish toxicity

1,2-benzisothiazol-3(2H)-one LC50: (Oncorhynchus mykiss (Rainbow trout)): = 11 mg/L (96 h)

12.2 Persistence and degradability

1,2-benzisothiazol-3(2H)-one

Biodegradation = 0.04 %

reaction mass of 5-chloro-2- methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3- one (3:1) Biodegradation = 60 %

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product/Packaging disposal

Do not empty into drains; dispose of this material and its container in a safe way. Waste disposal according to directive 2008/98/ EC, covering waste and dangerous waste.

Waste codes/waste designations according to EWC/AVV

080112 - waste paint and varnish other than those mentioned in 08 01 11



FG0-200griwecolor Stain primerVersion 1.0Revision date 18-Oct-2024

Other disposal recommendations

Non-contaminated packages may be recycled. Following consultation with waste management company and after solidification, landfill together with household waste.

SECTION 14: Transport information

14.1 UN number or ID number

not applicable

14.2 UN proper shipping name

Land transport (ADR/RID)

No dangerous good in sense of these transport regulations.

Sea transport (IMDG)

No dangerous good in sense of these transport regulations.

Air transport (ICAO-TI / IATA-DGR)

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

not applicable

14.4 Packing group

not applicable

14.5 Environmental hazards

Land transport (ADR/RID) Sea transport (IMDG) not applicable not applicable

14.6 Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

14.7 Maritime transport in bulk according to IMO instruments

No transport as bulk according to IBC Code.

14.8 Additional information

Land transport (ADR/RID) not applicable Sea transport (IMDG) not applicable Air transport (ICAO-TI / IATA-DGR) not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable. Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC value: 1 g/l

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

VOC limit value: 2004/42/IIA(g): 30 g/l (2010)

Maximum VOC content of the product in a ready to use condition: 1 g/L

This product meets the requirements of Regulation (EC) No. 1935/2004 on the limitation of VOC content.

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive] Hazard categories / Named dangerous substances

This product is not classified according to Directive 2012/18/EU.

National regulations



ections 2 to 15

FG0-200	griwecolor Stain primer
Version 1.0	Revision date 18-Oct-2024

Print date 18-Oct-2024

Observe in addition any national regulations!

SECTION 16: Other information

List of relevant hazard statements and/or precautionary statements from s		
H301	Toxic if swallowed.	
H302	Harmful if swallowed.	
H310	Fatal in contact with skin.	
H311	Toxic in contact with skin.	
H314	Causes severe skin burns and eye damage.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H330	Fatal if inhaled.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
EUH071	Corrosive to the respiratory tract.	

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

4

not applicable

Key literature references and sources for data

Data arise from reference works and literature.

Abbreviations and acronyms

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

OEL: Occupational Exposure Limit Value

- BLV: Biological limit values
- CAS: Chemical Abstracts Service

CLP: Classification, Labelling and Packaging

CMR: Carcinogenic, Mutagenic and Reprotoxic

DIN: German Institute for Standardization / German industrial standard

DNEL: Derived No-Effect Level

EAKV: European Waste Catalogue Directive

EC: Effective Concentration

EC: European Community

EN: European Standard

EU/EEA: European Community

IATA-DGR: International Air Transport Association – Dangerous Goods Regulations

IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk

ICAO-TI: International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air IMDG Code: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

LC: Lethal Concentration

LD: Lethal Dose

MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships OECD: Organisation for Economic Cooperation and Development PBT: persistent, bioaccumulative, toxic PNEC: Predicted No Effect Concentration REACH: Registration, Evaluation and Authorization of Chemicals RID: Regulations concerning the International Carriage of Dangerous Goods by Rail UN: United Nations VOC: Volatile Organic Compounds

vPvB: very persistent and very bioaccumulative

Indication of changes

* Data changed compared with the previous version.

Additional information

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.