Telefon +49 7707 9904-0 info@griwecolor.de www.griwecolor.de



Technical Data Sheet

Last revision: 10.12.2021

Plaster Primer

General Information

Article number:	PG1-200
Usage:	White-pigmented, unsaponifiable and adhesion promoting basic or intermediate coating with fine grain for all types of plaster. Prevents exsiccation when applying subsequent systems.
Weather-resistance:	Weather resistant according to DIN EN 18363 - 3.1.10.3.
VOC:	EU limit value of the product (cat. A/g): 30 g/l (2010). This product contains max. 12 g/l VOC.
Basis:	Acrylic copolymere dispersion, titanium dioxide and natural fillers.

Physical properties

Colour:	white
Gloss level:	mat
Density:	approx. 1.4 g/ml
Consumption:	Number of coats: 1 On smooth surfaces 150 - 200 g/m² for one coat of paint.
Covering rate:	1 litre covers approx. 5 - 6 m ² (one coat of paint)
Application	
Application:	Please stir up before use. Please pay attention to a uniform layer that is free of gaps. Only use clean working equipment.
Substrates:	Plasters. The surfaces must be sustainable, clean, dry and free from dirt, oil and grease and other separating substances. Existing coatings should be tested for sustainability and coats with unsuitable adhe- sion must be removed completely.
Thinning:	Not necessary. If required add maximal 8 % of water.
Processing equipment:	Brush or roller.
	Select equipment according to final rendering. The finer the final rendering is, the finer the tool should be.
Processing temperature:	Minimum +5 °C air and object temperature.
Drying:	Can be worked over after 12 hours drying time. Please ensure adequate ventilation.
Clean-Up:	Immediately in the wet state with water, if necessary in addition with a household detergent.

Telefon +49 7707 9904-0 info@griwecolor.de www.griwecolor.de



Technical Data Sheet

Last revision: 10.12.2021

Plaster Primer

Consignment & Storage

Packaging:	Trading units with 25 kg content.
Storage:	Keep dry and cool, but frost free! The product can be stored for a minimum of 9 months when kept sealed in the original container. Once the container is opened or diluted, use it soon and keep it tightly closed for storage. Keep out of reach of children.
Disposal:	Completely emptied containers can be recycled. Containers with hardened remains are residual waste. Containers with liquid re- mains are special waste and should be disposed at special collect- ing points according to the locally valid laws on waste disposal. You will find further information regarding the correct disposal on our MSDS.

Hazardous warning

No labelling required as product is non-hazardous. Please also follow the instructions on the MSDS.

You want advice?

Get in touch with us. We are looking forward to your inquiry.