

Wood primer

General Information

Article number:	HG1-200
Usage:	Special, water-based insulating and blocking primer against wood components for all domestic wood. Prevents perfusion of wood components when applying further coats of the system range griwecryl Water-based coating and griwecolor Wood protection.
VOC:	EU limit value of the product (cat. A/g): 30 g/l (2010). This product contains max. 1 g/l VOC.
Basis:	Modified acrylic dispersion

Physical properties

Colour:	white
Density:	approx. 1.03 g/ml
Consumption:	Number of coats: 1 According to the surface 80 - 120 ml/m ² for one coat of paint.
Covering rate:	1 litre covers approx. 10 m ² (one coat of paint).

Application

Application:	Please stir up before use. Please pay attention to a uniform layer that is free of gaps. Only use clean and dry working equipment, as griwecolor Wood primer is incompatible with other dispersion paints.
Substrates:	All types of domestic soft and hardwood, OSB, chipboard. The surfaces must be sustainable, clean, dry and free from dirt, oil and grease and other separating substances. Existing coatings should be grinded, tested for sustainability and coats with unsuitable adhesion must be removed completely.
Recommended treatment:	Inside: Wood primer HG0-200 (1 coat) griwecryl Water-based coating (1 - 2 coats) Outside: Wood primer HG0-200 (1 coat) griwecolor Wood protection(2 - 3 coats)
Thinning:	Not necessary, product is ready to use.
Processing equipment:	Brush, roller or suitable spraying machines.
Processing temperature:	Minimum +5 °C air and object temperature.

Wood primer

Drying:	Can be worked over after 24 hours drying time (relative air humidity up to 50 %).
Clean-Up:	Immediately in the wet state with water, if necessary in addition with a household detergent.

Consignment & Storage

Packaging:	Trading units with 1 l, 2,5 l, 5 l or 10 l content.
Storage:	Keep dry and cool, but frost free! The product can be stored for a minimum of 9 months when kept sealed in the original container. Once the container is opened or diluted, use it soon and keep it tightly closed for storage. Keep out of reach of children.
Disposal:	Completely emptied containers can be recycled. Containers with hardened remains are residual waste. Containers with liquid remains are special waste and should be disposed at special collecting points according to the locally valid laws on waste disposal. You will find further information regarding the correct disposal on our MSDS.

Hazardous warning

No labelling required as product is non-hazardous.
Please also follow the instructions on the MSDS.

**If you need assistance, we will be pleased to be at your service at any time.
Please contact us.**

Our technical data sheets and brochures are to inform you to the best of the company's knowledge.
However, they are not legally binding.